

CITED BY APPLICANT




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>G03B 21/10, G02B 27/00, 27/18, H04N 9/31</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/08141</b> <b>(43) International Publication Date:</b> 26 February 1998 (26.02.98)
<b>(21) International Application Number:</b> PCT/GB96/02079 <b>(22) International Filing Date:</b> 23 August 1996 (23.08.96) <b>(71)(72) Applicant and Inventor:</b> COLCLOUGH, Robin, Christopher [GB/GB]; 6 Hill Street, Mumbles, Swansea, W. Glamorgan SA1 4E11 (GB). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> HUXFORD, Roger, Brian [GB/GB]; 26 Park Close, Burgess Hill, West Sussex RH15 8HL (GB). <b>(74) Agents:</b> CRUMP, Julian, Richard, John et al.; F.J. Cleveland & Company, 40-43 Chancery Lane, London WC2A 1JQ (GB).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** IMAGE PROJECTING APPARATUS**(57) Abstract**

The present invention provides an image projecting apparatus (10), particularly a rear screen projecting apparatus, comprising a projecting lensing means (20) for projecting an image of an illuminated object, a screen (18), and reflecting means (30) for reflecting light from the projecting lensing means onto the screen; wherein the reflecting means is positioned off-centre with respect to the screen and asymmetric diverging lensing means (30) are provided for magnifying further the image reflected by the reflecting means onto the screen, the lensing power of the diverging lensing means varying across the area thereof, such that for each point on the diverging means, the combined focal length of the projecting lensing means and diverging lensing means is adjusted according to the length of the optical path between the projecting lensing means and the screen via that point, thereby to reduce optical distortion of the image on the screen. In some embodiments, said diverging lensing means may comprise a toroidal aspheric mirror or a complex aspheric mirror.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

IMAGE PROJECTING APPARATUS

The present invention relates to an image projecting  
5 apparatus, particularly the rear screen projector.

In its simplest form, a conventional rear screen  
projector comprises a translucent screen and a projecting  
lensing means for projecting an image of an illuminated  
10 object onto the screen. Typically the screen will  
comprise a composite construction consisting of a Fresnel  
lens and a lenticular lens screen. The projecting  
lensing means is positioned to one side of the screen,  
whilst the image is viewed from the opposite side. In  
15 order to avoid distortion of the image, the projecting  
lensing means is positioned and oriented such that the  
optical axis of the beam emitted by the projecting  
lensing means is disposed along a line which passes  
perpendicularly through the screen. The projecting  
20 lensing means may comprise a cathode ray tube (CRT), flat  
panel LCD or a conventional photographic transparency  
projector. Usually, the projecting lensing means will  
incorporate a source for illumination, and means for  
changing the object to be displayed. The principal  
25 disadvantage of this kind of rear screen projector is  
that the projecting lensing means has to be positioned

at a substantial distance from the screen in order to obtain satisfactory magnification of the image. This makes such rear screen projectors very large and cumbersome if a screen of reasonable dimensions is required.

Attempts have been made previously to reduce the overall dimensions of rear screen projectors without sacrificing screen size. US-A-5274406, for example, discloses a rear screen projector in which the light emitted by the projecting lensing means is reflected onto the screen by a mirror. The use of the mirror enables the apparatus to be accommodated within a reduced volume without diminishing the optical path length between the lensing projecting means and the screen. The angle subtended by the mirror and screen is less than  $45^\circ$ , and the mirror is therefore shaped, so as to reduce trapezoidal distortion of the image. The mirror of the apparatus disclosed by US-A-5274406 is positioned centrally with respect to the screen, and does not serve to magnify the image.

According to Japanese laid-open patent application no. 62-31838, the separation of the mirror and screen in an arrangement similar to that disclosed by US-A-5274406 may be reduced by adopting a convex mirror for magnifying

the image reflected by the mirror. According to JP62-31838 however, the mirror must subtend an angle of  $45^\circ$  with the screen.

5 It is an object of the present invention to provide an improved image projecting apparatus. In particular, it is an object of the invention to provide a image projecting apparatus which can be made more compact as compared with the apparatus known from the prior art,  
10 without sacrificing screen size or image quality.

It is a further object of the invention to provide an image projecting apparatus, particularly a rear screen projector, which can be accommodated within a housing in  
15 which the screen occupies substantially the whole of one face of the housing, and the apparatus can be accommodated within an area which is coterminous with the screen.

20 Another object of the invention is to provide a novel lensing mirror which can be used in the manufacture of a compact image projecting apparatus.

In one aspect of the present invention therefore there  
25 is provided an image projecting apparatus, particularly a rear screen projecting apparatus, comprising a

projecting lensing means for projecting an image of an illuminated object, a screen, and reflecting means for reflecting light from the projecting lensing means onto the screen, wherein the reflecting means is positioned  
5 off-centre with respect to the screen, and asymmetric diverging lensing means are provided for magnifying further the image reflected by the reflecting means onto the screen, the lensing power of the diverging lensing means varying across the area thereof, such that for each  
10 point on the diverging lensing means, the combined focal length of the projecting lensing means and diverging lensing means is adjusted according to the length of the optical path between the projecting lensing means and the screen via that point, thereby to reduce optical  
15 distortion of the image on the screen.

Said diverging lensing means will be positioned at or towards a position at which the image projected by the projecting lensing means is focused, so that the light  
20 incident on each point of the diverging lensing means will correspond to a discrete part of the image. In this way, the lensing power of the diverging lensing means at each point can be pre-selected independently of the rest of diverging lensing means to adjust the  
25 magnification of the corresponding part of the image, so that the image is projected substantially uniformly onto

the screen.

Preferably, the overall magnifying power of the diverging lensing means will be such that the divergence of the beam projected by the projecting lensing means is increased between two and twelve-fold by the diverging lensing means. Typically, the intrinsic field of view of the beam emerging from the projecting lensing means may be in the range  $10^{\circ}$  to  $30^{\circ}$ , and the intrinsic field of view of the beam treated by the diverging lensing means may be in the range  $60^{\circ}$  to  $100^{\circ}$ . The width of the diverging lensing means may therefore be about 10 to 40% of the width of the screen, typically about 25% or less. Moreover, the projecting lensing means can be designed to have zero or nearly zero vignetting, thus minimising the variation of illumination across the screen.

Said diverging lensing means and screen may be positioned with respect to one another such that the image on the screen is magnified between two and twenty times, typically ten times, as compared with the size of the image which is incident on the diverging lensing means.

Said screen will usually be a planar Fresnel lens/lenticular lens screen composite and will be oriented obliquely with respect to the reflecting means.

Said screen may be oriented such that a line on the screen, which line is disposed parallel to the projection of the optical axis between the projecting lensing means and the reflecting means onto the screen, subtends an angle of between  $0^{\circ}$  and  $45^{\circ}$  to the said optical axis.

Said projecting lensing means may be disposed juxtaposed one end of the screen, and the reflecting means may be disposed juxtaposed an opposing end of the screen. The optical path between the projecting lensing means, the reflecting means and the one end of the screen may be greater than the optical path to the opposing end of the screen. The ratio of these two optical paths will usually be in the range 1.0 to 2.0, preferably 1.1 to 1.6.

15

In a different aspect of the present invention, the image projecting apparatus may further comprise a housing, and the screen may occupy substantially the whole of one face of the housing. Said projecting lensing means, reflecting means and diverging lensing means may be accommodated within the housing within an area which is coterminous with the screen.

In another aspect of the present invention, the reflecting means may comprise a substantially planar mirror, and the diverging lensing means may comprise an

asymmetrical diverging lens positioned adjacent to the planar mirror, typically a concave diversing lens.

In yet another aspect of the present invention however  
 5 the reflecting means and diverging lensing means may be constituted by an asymmetrical diverging lensing mirror. Said lensing mirror may be symmetrical about a plane which is disposed normally to the screen, which plane contains the optical axis between the projecting lensing  
 10 means and the mirror. The profile of the reflecting surface of the mirror in section on this plane will be generally convex, with the radius of curvature varying across the surface of the mirror, from one end where light is reflected towards the one end of the screen  
 15 where the radius of curvature will be lower than at the other end where light is reflected onto the said opposing end of the screen. The reflecting surface of said lensing mirror may have a complex aspheric shape, which may be defined by the following complex polynomial:-

$$z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + a_2r^2 + a_3r^3 + a_4r^4 + a_5r^5 + a_6r^6 + \dots$$

20

wherein:-  $a_2, a_3, a_4, a_5, \dots$  are the aspheric coefficients,  
 $K$  = Conic Constant

8

$$r^2 = x^2 + y^2,$$

$c$  = bone curvature of the surface

(1/bone radius),

$z$  is the optical axis,

5  $x$  is an axis normal to the optical axis  
and parallel to the screen, and

$y$  is an axis normal to the  $x$  and  $z$  axes.

Alternatively, said asymmetrical diverging lensing mirror  
10 may comprise a toroidal aspheric mirror, the reflecting  
surface of which may be defined by the following  
formula:-

$$z = \frac{c_x x^2 + c_y y^2}{1 + \sqrt{1 - (1 + k_x)(c_x x)^2 - (1 + k_y)(c_y y)^2}} + a_4 x^4 + a_6 x^6 + a_8 x^8 + a_{10} x^{10} + b_4 y^4 + b_6 y^6 + b_8 y^8 + b_{10} y^{10}$$

15 wherein:-  $x, y$  and  $z$  are as defined above,

$a_4, a_6, a_8, a_{10}, b_4, b_6, b_8$  and  $b_{10}$  are aspheric  
coefficients, and  $c_x, c_y$  = bone curvatures of the surface  
along the  $x$  and  $y$  axes.

20 It will be appreciated that the convex surface of the  
lensing mirror may have the effect of defocussing the  
light reflected towards the screen.

Accordingly, in yet another aspect of the present invention, said diverging lensing means may comprise refocusing means for refocusing the light treated by the diverging lensing means. Said refocusing means may  
5 comprise a transparent refractive coating formed on the surface of the diverging lensing mirror or diverging lens, which transparent coating has a refractive index and surface profile which is controlled for refocusing the light treated by the diverging lensing means. The  
10 thickness of the coating may be substantially constant across the surface of the diverging lensing means. Alternatively the thickness of the coating may be varied, so as to control the refocusing power of the coating. In particular, the degree of defocussing occasioned by  
15 the diverging lensing mirror or diverging lens will vary according to the radius of curvature thereof, and the surface profile of the coating at each point on the diverging lensing means may therefore be pre-selected so that the refocussing power of the coating at that point  
20 compensates for the degree of defocussing of the corresponding part of the image.

Said coating may, in some embodiments, be formed as a plurality of contiguous lenticular lenslets provided on  
25 the surface of the diverging lensing means. The lensing power of each lenslet may be pre-selected according to

the position of the lenslet on the surface of the diverging lens or mirror. Said lenslets may be of uniform size, such that the density of levels per unit area is substantially constant across the surface of the lensing means. Alternatively the size and density of the lenslets may vary, with smaller lenslets being used in greater concentration at those parts of the lensing mirror or lens where the shape of the latter is most complex.

It may be the case that when lenslets of this kind are used on the surface of a diverging lensing mirror in accordance with the present invention, some light will be incident on one lenslet and will be reflected by the mirror through a neighbouring lenslet. This will lead to some scattering of the light which passes through the marginal portions of the lenslets. To reduce this problem, the thickness of each lenslet at its extremities may be minimized or reduced to zero. Alternatively, excess coating material could be removed from the margins of each lenslet after application of the coating to the mirror by laser etching. Masking means may be provided juxtaposed the boundary of each lenslet for reducing or preventing the transmission of light which passes through more than one lenslet. Said masking means may comprise a non-reflecting mask applied to the mirror surface, or

11

an optically-absorbing mask applied to the coating surface, juxtaposed the boundary of each lenslet.

Following is a description by way of example only with  
5 reference to the accompanying drawings of methods of carrying the present invention into effect.

In the drawings:-

10 Figure 1 shows a sectional view through a rear screen projector including a diverging lensing mirror in accordance with the present invention.

Figure 2 shows a detail of a plane mirror plus diverging  
15 lens which may be incorporated in the projector of Figure 1 in place of the mirror.

Figure 3 is an optical diagram of a different rear screen projector incorporating a diverging lensing mirror  
20 according to the present invention.

Figure 4 is a schematic, isometric view of the reflective surface of a diverging lensing mirror according to the  
invention.

25

Figure 5 is another optical diagram of the rear screen

projector of Figure 3 which shows how the diverging lensing mirror causes some defocussing of the light incident thereon.

5 Figure 6 is an optical diagram of another rear screen projector according to the invention, which projector incorporates a mirror having an optical coating thereon.

Figure 7 is an enlarged detail of the mirror and coating  
10 of Figure 6.

Figures 8A to 8E show various alternative mirror coatings for incorporation in the projector of Figure 6.

15 Figures 9A and 9B show further alternative, lenticular mirror coatings for the projector of Figure 6, which coatings comprise a plurality of contiguous lenslets.

Figure 10 shows a sectional view through a mirror having  
20 a lenticular thereon coating of the kind shown in Figure 9A or 9B.

Figure 11 is a sectional view through another mirror having a different lenticular coating formed thereon.

25

Figure 12 shows an optical diagram of the lenticular

13

mirror coatings of Figures 9A, 9B and 10, which shows how light may be scattered at the boundaries between contiguous lenslets.

5 Figure 13 shows a sectional view through another lenticular mirror coating which has been treated by laser etching to reduce boundary scattering.

10 Figure 14A shows a sectional view through yet another mirror having a lenticular coating thereon and a non-reflective mask juxtaposed the boundary between two neighbouring lenslets.

15 Figure 14B shows a sectional view through yet another mirror having a lenticular coating thereon and an optically-absorbing mask applied to the surface of the coating along the boundary between two contiguous lenslets.

20 Figure 15 is a sectional view of a projection lens combination suitable for use in a rear screen projector of the invention.

25 A rear screen projector (10) according to the invention comprises a generally rectilinear housing (12) of rectangular cross-section. Said housing (12) comprises

14

two opposing short walls (14) and two opposing long walls (16). One of said long walls is cut-out to accommodate a rectangular, translucent screen (18) which occupies substantially the whole area of the one long wall (16).

5 Said screen (18) consists of laminate comprising a Fresnel lens (19A) and a lenticular lens screen (19B). Such composite screens are well known in the art.

10 Said housing (12) accommodates a projection device (20) which is disposed juxtaposed the other long wall (16) remote from said screen (18) and towards one of the short walls (14).

15 Said projection device may comprise a CRT, flat panel LCD, DMD, or plasma or FED display device. Alternatively, said projection device (20) may comprise a conventional slide/film projector. Whichever form of projection device is employed, it will comprise a combination of projection lenses (22) such, for example, 20 as the lens combination shown in Figure 11 for magnifying and focusing an image of an object. Said projection lenses (22) have a focal plane (24) which is disposed adjacent to the opposing short wall (14) of the housing (10) as shown in Figure 1. Said projection device (20) 25 generates a divergent beam (26) which extends from the projection lenses (22) towards the focal plane (24) and

15

has an intrinsic field of view,  $\alpha$ , in the range  $10^\circ$  to  $25^\circ$ , typically  $15^\circ$  to  $20^\circ$ .

Juxtaposed said focal plane (24), the housing (10)  
5 accommodates a diverging lensing mirror (30). Said beam  
(26) is incident on a generally convex surface (32) of  
the mirror (30), and is thereby reflected towards the  
screen (18).

10 Said mirror (30) is symmetrical about a plane which is  
normal to the screen (18), which plane contains the  
optical axis (28) of the beam (26). In this plane the  
mirror (30) has a width less than about 25% of the width  
of the screen (18). The mirror (30) serves to magnify  
15 substantially the image projected by the projecting  
device (20) such that the beam reflected by the mirror  
(30) has an intrinsic field of view,  $\beta$ , in the range  $60^\circ$   
to  $100^\circ$ , typically about  $80^\circ$  to  $85^\circ$ . It will be  
appreciated that the optical path taken by light from the  
20 projecting device (20) to the mirror and thence to a  
first end (34) of the screen (18), which first end (34)  
is juxtaposed the projecting device (20), will be  
substantially longer than the optical path taken by light  
from the projecting device (20) to the opposing second  
25 end (36) of the screen (18). The convex surface (32)  
of the mirror (30) is profiled such that the lensing

power of the mirror (30) at each point at its surface (32) is determined according to the optical path length between the projecting device (20) and screen (18) via that point. The radius of curvature of each point on the surface (32) of the mirror is thus pre-selected, so that the image is magnified substantially uniformly onto the screen (18). The radius of curvature of the surface (32) is thus greater at the end of the mirror juxtaposed the projecting device (20) as compared with the radius of curvature at the opposing end of the mirror (30) where the light incident thereon has the shortest optical path.

In an alternative embodiment as shown in Figure 2, the diverging lensing mirror (30) may be replaced by a planar mirror (129) positioned with juxtaposition with the focal plane (24), which mirror (129) serves merely to reflect the light emerging from the projecting device (20) towards the screen (18), and a generally concave, asymmetric diverging lens (130) which serves to magnify the image reflected by said mirror (129). The lensing power of the diverging lens (130) varies across the surface (132) thereof in the same way as the diverging lensing mirror (30) in the previous embodiment, so as to ensure substantially uniform magnification of the projected image on the screen (18), thereby to reduce or substantially eliminate optical distortion of the image.

In the two embodiments described above, the screen (18) is oriented such obliquely with respect to the mirror (30;129) that a line on the screen (18), which line is parallel to a projection of the optical axis (28) onto the screen, is substantially parallel to the said optical axis (28).

In a different embodiment as shown in Figure 3, this line subtends an angle of about  $30^{\circ}$  to the optical axis (28). It will be appreciated by a person skilled in the art however that this angle may in fact vary between  $0^{\circ}$  and as much as, say,  $60^{\circ}$  without departing from the principles of this invention. Naturally, as the orientation of the screen (18) is varied with respect to the mirror (30) or mirror plus lens combination (129,130), the surface profile of the mirror (30) or lens (130) will vary to compensate for the concomitant changes in the optical path lengths between the projecting device (20) and screen (18).

20

An example of a suitable asymmetric diverging lensing mirror (30) for use in the embodiments of Figure 1 or Figure 3 is illustrated in Figure 4. This diverging lensing mirror (30) has a toroidal aspherical mirrored surface (32) which may be defined by the following formula:-

25

$$z = \frac{c_x x^2 + c_y y^2}{1 + \sqrt{1 - (1 + k_x)(c_x x)^2 - (1 + k_y)(c_y y)^2}} + a_4 x^4 + a_6 x^6 + a_8 x^8 + a_{10} x^{10} + b_4 y^4 + b_6 y^6 + b_8 y^8 + b_{10} y^{10}$$

wherein:-  $a_4, a_6, a_8, a_{10}, b_4, b_6, b_8$  and  $b_{10}$  are aspheric coefficients.

- 5                     $z$  is the optical axis,  
                      $x$  is the axis normal to the optical axis  
                     and parallel to the screen,  
                      $y$  is the axis normal to the  $x$  and  $z$  axes.  
                      $c_x$  and  $c_y$  are the bone curvature of the  
 10 surface along the  $x$  and  $y$  axes respectively.

In the present example, said toroidal aspheric mirror (30) has the following coordinates:-

5

10

15

20

25

X = 0		X = ± 23.18		X = ± 40.45		X = ± 57.97	
Y	Z	Y	Z	Y	Z	Y	Z
98.89	150.18	98.89	150.17	97.10	148.38	97.41	145.76
87.48	147.68	87.47	147.60	87.68	145.65	87.98	142.83
77.98	145.12	78.00	144.99	78.20	142.88	78.48	139.82
68.45	142.55	68.47	142.30	68.66	139.99	68.93	136.69
58.88	139.93	58.88	139.51	69.06	136.99	59.31	133.44
49.21	137.22	49.24	136.69	49.40	133.83	49.63	130.02
39.60	134.38	39.54	133.47	39.68	130.48	39.87	126.39
29.73	131.38	29.77	130.12	29.89	126.88	30.04	122.53
19.90	128.04	19.94	126.44	20.02	122.98	20.12	118.40
9.99	124.32	10.02	122.38	10.06	118.73	10.11	113.97
0.00	120.00	0.00	117.87	0.00	114.10	0.00	109.28
-10.10	114.87	-10.13	112.90	-10.17	109.12	-10.23	104.29
-20.35	108.88	-20.38	107.54	-20.47	103.86	-20.58	99.16
-30.79	101.24	-30.77	101.98	-30.89	98.51	-31.05	94.02
-41.47	92.42	-41.28	96.53	-41.43	93.30	-41.63	89.06
-52.44	82.24	-51.89	91.58	-52.07	88.55	-52.30	84.50
-63.73	70.84	-62.56	87.60	-62.76	84.67	-63.04	80.63
-76.38	58.35	-73.60	79.98	-73.87	76.70	-74.24	72.27
-87.41	44.94	-84.94	71.24	-85.28	67.63	-86.74	62.73
-99.84	30.73	-96.52	62.16	-96.93	58.26	-97.49	52.94
-112.69	15.82	-108.34	52.78	-108.83	47.60	-109.50	42.90

Alternatively, a complex aspheric mirror may be used which may be defined by the following polynomial:-

$$z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + a_2r^2 + a_3r^3 + a_4r^4 + a_5r^5 + a_6r^6 + \dots$$

wherein:-

x, y and z are as defined above,

$$r^2 = x^2 + y^2,$$

$a_2, a_3, a_4, a_5, \dots$  are the aspheric coefficients

k = conic constant,

5

c = bone curvature of the surface (1/bone radius).

10 Naturally, for any specified embodiment, the actual surface configuration of the toroidal or aspheric mirror may be mapped using computer modelling, and the applicants have found that the polynomial for the complex aspheric mirror supports more aspheric coefficients to allow greater control over the shaping of the mirror.

15 With reference to Figure 5, it will be appreciated that the convex surface (32) of the diverging lensing mirror (30) or diverging lens (130) will have a defocussing effect on the light reflected by the mirror (30;129) onto the screen (18). The magnitude of this defocussing  
20 effect will depend on the radius of curvature of the mirror surface (32), and will thus vary across said surface (32).

Preferably therefore the surface (32) of the mirror (30) or diverging lens (130) will be coated with a transparent refracting material as shown in Figure 6. Light incident on the mirror (30) or lens (130) will thus be refracted by the coating (40). The degree of refraction will depend on the surface profile and refractive index of the coating for each point on the surface of the mirror (30) or lens (130). The profile of the coating may thus be pre-selected to cause refocusing of the light reflected by the mirror (30), or transmitted by the lens (130), onto the screen (18). An enlarged view of this is shown in Figure 7.

The thickness of the coating (40) may be substantially uniform across the surface (32) of the mirror (30) or lens (130), and this will produce a mild refocusing effect in use. Alternatively, the thickness of the coating may be non-uniform such that the surface profile of the coating is shaped independently of the surface configuration (32;132) of the mirror (30) or lens (130). Preferably the surface profile of the coating (40) may be calculated such that the refocussing power of the coating at each point on the surface of the mirror (30) or lens (130) substantially compensates for the defocussing of the corresponding part of the image, which defocussing is caused by the juxtaposed part of the mirror (30) or lens (130). Various

alternatives are shown in Figures 8A to 8E. In Figure 8A, no coating is used, and this Figure shows the magnifying effect of the mirror surface (32). In Figure 8B, the coating (40) has a surface (42) of greater radius of curvature than the surface (32) of the mirror (30). In Figure 8C, the thickness of the coating (40) is uniform across the surface of the mirror (30), and in Figure 8D the surface (42) of the coating (40) has a smaller radius of curvature than the surface (32) of the mirror (30). In Figure 8E, the thickness of the coating (40) is irregular.

As a further alternative, the coating (40) on the surface (32;132) of the mirror (30) or lens (130) may be formed into a plurality of contiguous lenticular lenslets (44) as shown in Figures 9A or 9B and Figure 10. The lenslets (44) may be square, rectangular or hexagonal, or any other tessalating shape. The surface profile of each lenslet (44) may be pre-selected independently of the other lenslets (44), so as to provide a refocusing power which corresponds to the strength of defocusing caused by the surface (30;132) of the mirror (30) or lens (132) adjacent the lenslet (44).

As shown in Figures 9A and 9B, the lenslets (44) may be of uniform shape and configuration. Alternatively, as shown in Figure 11, the size (and the density per unit area) of

the lenslets may vary across the surface of the lens (130) or mirror (30). In particular, it will be appreciated that where the curvature, and thus defocusing power, of the mirror (30) or lens (130) changes most greatly within unit area, there smaller lenslets (44) of varying refocusing power will be required so as to ensure that the refocusing power of each lenslet is properly matched to the defocusing action of the juxtaposed part of the mirror (30) or lens (130). Thus, in Figure 11, it will be seen that the smallest lenslets (44) are provided juxtaposed the end of the mirror (30) remote from the projection lenses (22), where the surface configuration of the mirror (30) is most convoluted. Here the defocusing power of the mirror (30) varies most with distance along the surface (32) of the mirror, and thus the refocusing power of the lenslets (44) is also required to be varied as greatly over the same area. Naturally, where the surface (32) of the mirror (30) is flatter, in this case towards the projection lenses (22), there the defocusing power of the mirror changes less dramatically across the surface (32), and thus the corrective refocusing power required also varies less with area, and so larger lenslets (44) can be employed.

In yet another alternative, the lenslets (44) may be manufactured independently from each other from any

suitable transparent, refracting material such, for example, as a synthetic plastics material, and then applied to the mirror (30) or lens (130) after manufacture.

5

As shown in Figure 12, a problem with the use of a lenticular coating (40) of the kind shown in Figures 9A, 9B and 10 is that light incident on one lenslet (44) juxtaposed the boundary (46) with another neighbouring lenslet (44) may be reflected by the mirror surface (32) through said neighbouring lenslet. This will cause an amount of scattering of the light reflected by the mirror. In Figure 12 the path which should be taken by the incident ray to achieve refocussing is marked "B", but the actual path taken, as a result of scattering, is marked "A".

In order to reduce the magnitude of the scattering, the thickness of the coating (40) at the boundaries (46) between contiguous lenslet (44) may be reduced to zero as shown in Figure 13. This may be achieved by laser etching after forming the coating (40) on the mirror (30).

Alternatively, the scattered light may be removed by applying a narrow non-reflecting mask (48) to the mirror surface (32) juxtaposed each boundary (40) between

neighbouring lenslets (44) as shown in Figure 14A, or by applying an optically-absorbing strip (49) to the surface (42) of the coating (40) along the boundary between each lenslet (44) and its contiguous lenslets as shown in  
5 Figure 14B.

It should be noted that the embodiments of the invention hereinbefore described may be operated with an object which is oriented normally with respect to the optical  
10 axis (28). Alternatively, the object may be inclined with respect to the optical axis (28), in which case the lenses (22) of the projection device (20) may be arranged to provide Scheimpflug Correction as shown in Figure 15, with a correspondingly inclined focal plane (24). In  
15 this case, the shape of the lensing mirror (30) or diverging lens (130) will be adjusted accordingly.

It has been found that the adoption of Scheimpflug Correction in this way may assist in correcting the  
20 distortion of the image.

The invention as hereinbefore described may provide an ultra-compact image projecting apparatus such as a rear screen projector, in which all the components of the  
25 projector can be accommodated within an area which is coterminous with the area of the screen. The optical path

length between the projection device (20) and the screen (18) is shortened by using a diverging mirror (30) or diverging lens (130) which is capable of magnifying greatly the image projected by the projection device onto the screen. The diverging mirror, or a separate diverging lens, is shaped asymmetrically to compensate for the optical distortion of the image caused by positioning the screen off-centre and inclined obliquely with respect to the mirror. The invention also provides novel forms of asymmetric diverging lensing mirror which are suitable for use in the projecting apparatus.

CLAIMS

1. An image projecting apparatus (10), particularly a  
5 rear screen projecting apparatus, comprising a projecting  
lensing means (20) for projecting an image of an  
illuminated object, a screen (18) and reflecting means  
(30;129) for reflecting light from the projecting lensing  
means onto the screen, wherein the reflecting means is  
10 positioned off-centre with respect to the screen and  
asymmetric diverging lensing means (30;130) are provided  
for magnifying further the image reflected by the  
reflecting means onto the screen, the lensing power of  
the diverging lensing means varying across the area  
15 thereof, such that for each point on the diverging  
lensing means, the combined focal length of the  
projecting lensing means and diverging lensing means is  
adjusted according to the length of the optical path  
between the projecting lensing means and the screen via  
20 that point, thereby to reduce optical distortion of the  
image on the screen.

2. Image projecting apparatus as claimed in claim 1  
wherein said diverging lensing means is positioned at or  
25 towards a position at which the image projected by the  
projecting lensing means is focused, so that the light

incident on each point of the diverging lensing means corresponds to a discrete part of the image.

3. Image projecting means as claimed in claim 1 or claim  
5 2 wherein the lensing power of the diverging lensing means at each point is pre-selected independently of the rest of the diverging lensing means so as to adjust the magnification of the corresponding part of the image, so that the image is projected substantially uniformly  
10 onto the screen.

4. Image projecting means as claimed in claim 1, claim  
2 or claim 3 wherein the overall magnifying power of the diverging lensing means is such that the divergence of  
15 the beam projected by the projecting lensing means is increased by between X2 and X12 by the diverging lensing means.

5. Image projecting apparatus as claimed in any  
20 preceding claim wherein the intrinsic field of view of the beam emerging from the projecting lensing means is in the range 10 to 30°, and the intrinsic field of view of beam treated by the diverging lensing means is in the range 60 to 100°.

25

6. Image projecting apparatus as claimed in any

preceding claim wherein said diverging lensing means and screen are positioned with respect to one another such that the image on the screen is magnified between 2 and 20 times, typically 10 times, as compared with the size of the image which is incident on the diverging lensing means.

7. Image projecting apparatus as claimed in any preceding claim wherein said screen is oriented such that a line on the screen, which line is disposed parallel to the projection of the optical axis between the projecting lensing means and the reflecting means onto the screen, subtends an angle of between 0 and 45° to the said optical axis.

15

8. Image projecting apparatus as claimed in any preceding claim wherein said projecting lensing means (20) is disposed juxtaposed one end (34) of the screen (18), and the reflecting means (30;129) is disposed juxtaposed an opposing end (36) of the screen, the optical path between the projecting lensing means, the reflecting means and the one end (34) of the screen being greater than the optical path to the opposing end (36) of the screen.

25

9. Image projecting apparatus as claimed in any

preceding claim further comprising a housing (12), said screen occupying substantially the whole of one face (16) of the housing.

- 5 10. Image projecting apparatus as claimed in claim 9 wherein said projecting lensing means, reflecting means and diverging lensing means are accommodated within the housing (12), within an area which is coterminous with the screen.

10

11. Image projecting apparatus as claimed in any preceding claim wherein said reflecting means comprises a substantially planar mirror (129), and the diverging lensing means comprises an asymmetrical diverging lens (130) positioned adjacent to the mirror.

15

12. Image projecting apparatus as claimed in any of claims 1 to 10 wherein the reflecting means and diverging lensing means are constituted by an asymmetrical diverging lensing mirror (30).

20

13. Image projecting apparatus as claimed in claim 12 wherein said lensing mirror has an asymmetrical convex shape.

25

14. Image projecting apparatus as claimed in claim 12

or claim 13, wherein said asymmetrical diverging lensing mirror comprises a complex aspheric mirror which has a reflecting surface defined by the formula:-

$$z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + a_2r^2 + a_3r^3 + a_4r^4 + a_5r^5 + a_6r^6 + \dots$$

5

wherein:-  $a_2, a_3, a_4, a_5, \dots$  are the aspheric coefficients,

$k$  = conic constant

$$r^2 = x^2 + y^2,$$

10

$z$  is the optical axis,

$x$  is an axis normal to the optical axis

and parallel to the screen,

$y$  is an axis normal to the  $x$  and  $z$  axes,

and

15

$c$  is the base curvature of the surface  
(1/base radius).

15. Image projecting apparatus as claimed in claim 12 or claim 13, wherein said asymmetrical diverging lensing mirror (30) comprises a toroidal aspheric mirror which has a reflecting surface defined by the formula:-

$$z = \frac{c_x x^2 + c_y y^2}{1 + \sqrt{1 - (1+k_x)(c_x x)^2 - (1+k_y)(c_y y)^2}} + a_4 x^4 + a_6 x^6 + a_8 x^8 + a_{10} x^{10} + b_4 y^4 + b_6 y^6 + b_8 y^8 + b_{10} y^{10}$$

wherein:-  $x, y$  and  $z$  are as defined above, and

$a_4, a_6, a_8, a_{10}, b_4, b_6, b_8$  and  $b_{10}$  are aspheric coefficients, and

$c_x$  and  $c_y$  are the base curvatures of the surface in the  $x$  and  $y$  axes respectively.

16. Image projecting apparatus as claimed in any preceding claim wherein said diverging lensing means comprises refocusing means for refocusing the light treated by the diverging lensing means.

17. Image projecting apparatus as claimed in claim 16 wherein said refocusing means comprises a transparent refractive coating (40) formed on the surface of the diverging lensing mirror or diverging lens, which transparent coating has a refractive index and surface profile which is controlled for refocusing the light treated by the diverging lensing means (30).

18. Image projecting apparatus as claimed in claim 17 wherein said coating (40) is formed as a plurality of contiguous lenticular lenslets (49) on the surface of the diverging lensing means.

19. Image projecting apparatus as claimed in claim 18 wherein the thickness of each lenslet (49) at its extremities (46) is minimized or reduced to zero.

5

20. Image projecting apparatus as claimed in claim 18 or claim 19 wherein masking means (48;49) are provided juxtaposed the boundary of each lenslet for reducing or preventing the transmission of light which passes through  
10 more than one lenslet.

21. Image projecting apparatus as claimed in claim 20 wherein said masking means comprises a non-reflecting mask (48) applied to the mirror surface, or an optically  
15 absorbing mask (49) applied to the coating surface, juxtaposed the boundary of each lenslet.






Figure 1

2/12




**Figure 2**




**Figure 3**


4/12




**Figure 4**



**Figure 5**



7/12



**Figure 7**

8/12




Figure 8b




Figure 8e




Figure 8c




Figure 8a






Figure 8d


9/12



**Figure 9b**




**Figure 9a**







**Figure 10**


Figure 11



11/12



12/12



**Figure 15**

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/GB 96/02079

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G03B21/10 G02B27/00 G02B27/18 H04N9/31

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 G03B G02B H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 003 080 A (MAIMAN THEODORE H ET AL) 11 January 1977 see column 7, line 40 - column 8, line 34 see abstract; figure 3	1-10,12, 13
A	---	11,14-21
X	EP 0 631 434 A (UNIC VIEW LTD) 28 December 1994 see column 14, line 56 - column 15, line 43; figures 19,20	1-10,12, 13
A	---	
A	US 4 078 860 A (GLOBUS RONALD P ET AL) 14 March 1978 see column 2, line 49 - column 4, line 19 see abstract; figures 1-3	1,11
	---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

11 April 1997

Date of mailing of the international search report

22.04.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Manntz, W

# INTERNATIONAL SEARCH REPORT

Int. Application No  
PCT/GB 96/02079

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 724 199 A (NIKON) 31 July 1996 see page 8, line 13 - page 9, line 15; figures 14-16 ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 011, no. 211 (P-594), 9 July 1987 & JP 62 031838 A (VICTOR CO OF JAPAN LTD), 10 February 1987, cited in the application see abstract ---	1
A	US 5 274 406 A (TEJIMA YASUYUKI ET AL) 28 December 1993 cited in the application see abstract; figures 12C,14A -----	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 96/02079

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4003080 A	11-01-77	DE 2624546 A FR 2313828 A JP 52014431 A	16-12-76 31-12-76 03-02-77
EP 0631434 A	28-12-94	CA 2126130 A CN 1104822 A JP 7244266 A	21-12-94 05-07-95 19-09-95
US 4078860 A	14-03-78	DE 2725444 A JP 958448 C JP 53034487 B JP 53055025 A	03-05-78 14-06-79 21-09-78 19-05-78
EP 0724199 A	31-07-96	JP 8203805 A	09-08-96
US 5274406 A	28-12-93	JP 1257834 A	13-10-89